

1	20	20	20
2	20	20	20
3	20	20	20
4	20	20	20
5	20	20	20
6	20	20	20
7	20	20	20
8	20	20	20
9	20	20	20
10	20	20	20
11	20	20	20
12	20	20	20
13	20	20	20
14	20	20	20
15	20	20	20
16	20	20	20
17	20	20	20
18	20	20	20
19	20	20	20
20	20	20	20
21	20	20	20
22	20	20	20
23	20	20	20
24	20	20	20
25	20	20	20
26	20	20	20
27	20	20	20
28	20	20	20
29	20	20	20
30	20	20	20
31	20	20	20
32	20	20	20
33	20	20	20
34	20	20	20
35	20	20	20
36	20	20	20
37	20	20	20
38	20	20	20
39	20	20	20
40	20	20	20
41	20	20	20
42	20	20	20
43	20	20	20
44	20	20	20
45	20	20	20
46	20	20	20
47	20	20	20
48	20	20	20
49	20	20	20
50	20	20	20
51	20	20	20
52	20	20	20
53	20	20	20
54	20	20	20
55	20	20	20
56	20	20	20
57	20	20	20
58	20	20	20
59	20	20	20
60	20	20	20
61	20	20	20
62	20	20	20
63	20	20	20
64	20	20	20
65	20	20	20
66	20	20	20
67	20	20	20
68	20	20	20
69	20	20	20
70	20	20	20
71	20	20	20
72	20	20	20
73	20	20	20
74	20	20	20
75	20	20	20
76	20	20	20
77	20	20	20
78	20	20	20
79	20	20	20
80	20	20	20
81	20	20	20
82	20	20	20
83	20	20	20
84	20	20	20
85	20	20	20
86	20	20	20
87	20	20	20
88	20	20	20
89	20	20	20
90	20	20	20
91	20	20	20
92	20	20	20
93	20	20	20
94	20	20	20
95	20	20	20
96	20	20	20
97	20	20	20
98	20	20	20
99	20	20	20
100	20	20	20

A rotor is disclosed for a super-conducting synchronous machine comprising: a rotor core; a super-conducting coil extending around at least a portion of the rotor core, said coil having coil side sections on opposite sides of said rotor core; a vacuum housing covering at least one of said coil side sections, and a conductive shield over said vacuum housing and coil side sections.